

TECHNICAL DATA SHEET

BONDING FELT - 25 kg

Issue 5 – October 2015

Uses: Intended for use in built-up roofing as an underlay or cap sheet. Using a traditional fibre based carrier, the membrane offers excellent application characteristics and is suitable in either repair applications or as part of built-up roofing.

Performance

Features: Correctly installed, Rose bonding felts will provide a long life to built-up roofing systems. The membrane is installed by using traditional hot bonding techniques described in BS Code of Practice 144 Part 3. It can be cut and formed using sharp hand tools.

Do not expose the membrane to hydrocarbon based solvent products.

Storage and Handling:

Do not drag rolls across rough surfaces, they should be lifted. Rolls should be stood on their ends on a dry surface. If using pallets do not stack more than two pallets high. Avoid mechanical damage and damp storage conditions.

Technical Performance Data (Typical):

Carrier:	380g/m ²
Roll Size:	10m
Nominal Roll Weight	25kg
Nominal M ² Weight:	2.5kg
Rolls Per Pallet:	30

Health & Safety: There are no harmful effects or Health + Safety Hazards related to Cromar Bonding Felts. However, we recommend that all installers observe and implement Health and Safety regulations in relation to the hot bonding material and heating equipment used.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.