



Wall Tile Grout Powder Technical Data Sheet

Description

Bartoline Waterproof Wall Tile Grout is a cement based powdered grouting compound. Can be used on joints up to 3mm. Suitable for use in kitchens, bathrooms and showers. Can be used internally or externally.

Directions

Preparation: Ensure tile adhesive is dry before grouting and remove any tile spacers.

Mixing: Add approximately 2 parts grout powder to 1 part cold water. Mix to a smooth paste. Before grouting, allow to stand for approximately 10 minutes, then re-stir.

Application:

Push grout into joints using a grout float. Leave for a few minutes to harden and remove excess with a damp cloth or sponge. After leaving the grout to harden slightly, use a grout shaper to finish off the joints and make them neat and tidy. Leave to fully harden overnight and polish with a dampened cloth. Protect grouted areas from water and frost until the grout is completely dry.

Cleaning & Storage

All tools and mixing bowls should be cleaned with water before the grout hardens. Store in a dry place, keeping sachet closed.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Fine Powder	Visual
Colour	White	Visual
Odour	Cement type	
Flash point	Not Applicable	
VOC content	None	
pH	11.5 – 12.5	280g powder to 90g water

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
500g Box	52853220	5010789853228	05010789616007	12	84	1008	14	6
2Kg Box	52853230	5010789853235	05010789601195	6	65	390	13	5

Customs Tariff Code

3214 9000

Shipping Classification

Non-Hazardous for shipping purposes