

TECHNICAL DATASHEET

Cromatorch Arcoflex SBS Underlay

Description & Uses

CROMATORCH ARCOFLEX is a waterproofing membrane made of distilled bitumen modified with SBS (styrene-butadiene-styrene) polymers that make it very elastic, resistant to thermal ageing and flexible at low temperatures. The elastomeric compound ensures ease of application, reduced consumption of gas and has excellent adhesion properties that ensure, when the membrane is properly installed, superior bonding and tightness of all joints and overlaps.

The carrier is made of glass fibre with longitudinal reinforcements which provide CROMATORCH ARCOFLEX with high dimensional stability, making it the ideal base sheet in various waterproofing systems.

CE Marked.

Product Details

Properties	Test Method	Unit	Details	Tol.
Tensile Strength (at break) L/T	EN12311-1	N/5 cm	300/200	±20%
Elongation (at break) L/T	EN12311-1	%	2/2	±1
Tear resistance (nail test) L/T	EN 12310-1	N	70/70	±30%
Resistance to static loading	EN12730 (A)	Kg	NPD	≥
Flexibility at low temperature	EN 1109	°C	-10	≤
Flow resistance at elevated temperature	EN1110	°C	90	≥
Watertightness (method A)	EN1928	kPa	60	≥
Resistance to water vapor diffusion (μ)	EN1931	-	20.00	-
Reaction to fire	EN13501-1	Class	E	-
Resistance to external fire	EN13501-5	Class	FROOF	-

Use & Application

CROMATORCH ARCOFLEX is recommended as a base sheet or intermediate layer in multi-layer waterproofing constructions for flat, pitched or vaulted roofs.

CROMATORCH ARCOFLEX must always be protected by a torch applied cap sheet membrane (the use of reflective paint is not recommended for this type of membranes). Direct exposure to UV should be avoided.

Subject to the type of substrate it shall be installed by means of a propane gas torch or approved adhesives.

Storage

Keep the rolls in the upright position, protected from the sun (temperature ranging between 0°C and 40°C) and well away from heat sources and electrical plant. No measures are needed to prevent the build-up of static electricity. Keep proper fire-fighting equipment available at all times.

Limitations

- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.