

TECHNICAL DATA SHEET

CromaVerge

Premium Universal Dry Verge

DESCRIPTION:

Universal quick and easy to install Dry Verge System that does not require separate left hand and right-hand units. This system is maintenance free, cost effective and supersedes the traditional mortar for pointing the verge.

MATERIAL:

PP Grey UV 20% MF Compound Type 16006

FEATURES:

A premium, universal dry verge system, no need for separate left or right-handed verges. Available in 4 popular colours.

- Universally handed – no need for left and right units
- Quick fit design – 36 units in under 5 minutes
- Versatile – fit to any type of roof tile
- High compression – roof tiles held firm in strong winds
- Zero maintenance – years of mortar free protection
- High quality – tough and UV stable plastic
- Mortar free – eaves remains protected but well ventilated

RECOMMENDED PARTS LIST:

(Items Available Separately)

- Verge unit
- Eaves Starter Kit
- Ridge Cap (half round and angled)
- Finishing Cap

PACKAGING:

Packaged in boxes of 40

LIMITATIONS:

Performance independently tested to BS8612

These are typical values produced for guidance and as a basis for evaluation and do not constitute any specific guarantee whatsoever

Date – 11/01/2016 10:04:47

Doc. No.

Property	Specification	Units	Standard
Melt Flow Index	10-15	g/10mins	ISO 113
Izod at Room Temperature notched	4.75+	KJ/m ²	ISO 180
Load at Peak	800 - 950	N	ISO/R 527
Flexural Modulus	1450 - 1650	N/mm ²	ISO 178
Filler	18 - 22	%	Internal Test

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com