



AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 8/27/2019 Revision date: 7/14/2020 Supersedes version of: 8/28/2016 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : AlphaChem 3 in 1 Wood Preserver Colours
Product code : LWU
Type of product : Biocidal products (e.g. Disinfectants, pest control), Solvents
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : A solvent based wood treatment containing actives for wood worm and dry rot

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Cromar Building Products
Units 3, 4, 5 Northside Ind Park
Selby Rd
DN14 0GH Whitley Bridge - United Kingdom
T 01977 663133 - F 01977 662186
www.cromarbuildingproducts.com

1.4. Emergency telephone number

Emergency number : 01977 663133 (Business hours only Mon-Fri 9am-5pm)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 1 H372
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

- : Danger
- : PROPICONAZOLE; M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE; Hydrocarbons C9-C12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%); LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY
- : H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
- : EUH208 - Contains PROPICONAZOLE(60207-90-1), M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE(52645-53-1). May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons C9-C12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)	(CAS-No.) 64742-82-1 (EC-No.) 919-446-0 (REACH-no) 01-2119458049-33	90 – 98	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY	(CAS-No.) 64742-82-1 (EC-No.) 265-185-4 (EC Index-No.) 649-330-00-2	0.5 – 1.2	Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
PROPICONAZOLE	(CAS-No.) 60207-90-1 (EC-No.) 262-104-4 (EC Index-No.) 613-205-00-0	0.5 – 1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE	(CAS-No.) 52645-53-1 (EC-No.) 258-067-9 (EC Index-No.) 613-058-00-2	0.2 – 0.3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=1000)
---	---	-----------	--

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness. There are potential chronic health effects to consider.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide. May release flammable gases.

5.3. Advice for firefighters

Precautionary measures fire	: Eliminate all ignition sources if safe to do so. This product is not to be used under conditions of poor ventilation.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Avoid contact with skin, eyes and clothing. Do not breathe vapours. Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Breathing apparatus. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Do not touch spilled material. Cover spill with non combustible material, e.g.: sand/earth. Evacuate unnecessary personnel. Ventilate area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Do not touch or walk on the spilled product. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not pierce or burn, even after use. Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Do not pierce or burn, even after use. Ensure good ventilation of the work station. Handle and open container with care. Use personal protective equipment as required. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Use only non-sparking tools. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep cool. Keep only in original container. Store in a well-ventilated place. Store locked up.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY (64742-82-1)

EU - Occupational Exposure Limits

Local name	White spirit Type 1
IOELV TWA (mg/m ³)	116 mg/m ³
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m ³)	290 mg/m ³
IOELV STEL (ppm)	50 ppm
Notes	skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

AlphaChem 3 in 1 Wood Preserver Colours

DNEL/DMEL (Workers)

Acute - local effects, inhalation	570 mg/m ³ C10-C14
Long-term - systemic effects, dermal	44 mg/kg bodyweight/day C10-C14
Long-term - systemic effects, inhalation	330 mg/m ³ C10-C14

DNEL/DMEL (General population)

Acute - local effects, inhalation	570 mg/m ³ C10-C14
Long-term - systemic effects, oral	26 mg/kg bodyweight/day C10-C14
Long-term - systemic effects, inhalation	71 mg/m ³ C10-C14
Long-term - systemic effects, dermal	26 mg/kg bodyweight/day C10-C14

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
					EN ISO 374

Eye protection:

Chemical goggles or safety glasses

Type	Use	Characteristics	Standard
			EN 166

Skin and body protection:

Wear suitable protective clothing

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: Colourless.
Odour	: characteristic. Pungent.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -20 °C @ 760 mm Hg
Freezing point	: No data available
Boiling point	: 153 – 200 °C
Flash point	: 40 °C Closed Cup
Auto-ignition temperature	: > 200 °C >200
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.231 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: 0.78 – 0.8 @ 15 C
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 1 – 2.5 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 7
Upper explosive limit (UEL)	: 0.6

9.2. Other information

VOC content : 795 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

No additional information available

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

AlphaChem 3 in 1 Wood Preserver Colours

LD50 oral rat	> 5000 mg/kg C9-C12
LD50 oral	1479 mg/kg Rat Permethrin
LD50 dermal rat	> 2000 mg/kg C9-C12
LD50 dermal	> 4000 g/kg Propiconazole
LC50 inhalation rat (mg/l)	> 5000 mg/kg C9-C12
LC50 inhalation rat (Vapours - mg/l/4h)	> 5800 mg/l/4h Propiconazole

Skin corrosion/irritation : Not classified
pH: Not applicable.

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified
pH: Not applicable.

Additional information : Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : May cause drowsiness or dizziness.

Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

AlphaChem 3 in 1 Wood Preserver Colours

Viscosity, kinematic	1 – 2.5 mm ² /s
----------------------	----------------------------

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

AlphaChem 3 in 1 Wood Preserver Colours

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

PROPICONAZOLE (60207-90-1)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE (52645-53-1)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

Hydrocarbons C9-C12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%) (64742-82-1)

Persistence and degradability	Not established.
-------------------------------	------------------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY (64742-82-1)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

AlphaChem 3 in 1 Wood Preserver Colours

Bioaccumulative potential	Not established.
---------------------------	------------------

PROPICONAZOLE (60207-90-1)

Bioaccumulative potential	Not established.
---------------------------	------------------

M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE (52645-53-1)

Bioaccumulative potential	Not established.
---------------------------	------------------

Hydrocarbons C9-C12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%) (64742-82-1)

Bioaccumulative potential	Not established.
---------------------------	------------------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY (64742-82-1)

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830





SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Additional information : Handle empty containers with care because residual vapours are flammable.
- Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1300	UN 1300	Not regulated	UN 1300	UN 1300
14.2. UN proper shipping name				
TURPENTINE SUBSTITUTE	TURPENTINE SUBSTITUTE	Not regulated	TURPENTINE SUBSTITUTE	TURPENTINE SUBSTITUTE
Transport document description				
UN 1300 TURPENTINE SUBSTITUTE, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1300 TURPENTINE SUBSTITUTE, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	Not regulated	UN 1300 TURPENTINE SUBSTITUTE, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1300 TURPENTINE SUBSTITUTE, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	Not regulated	3	3
		Not regulated		
14.4. Packing group				
III	III	Not regulated	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Not regulated	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

- Classification code (ADR) : F1
- Limited quantities (ADR) : 5I
- Excepted quantities (ADR) : E1
- Packing instructions (ADR) : P001, IBC03, LP01, R001
- Mixed packing provisions (ADR) : MP19
- Portable tank and bulk container instructions (ADR) : T2
- Portable tank and bulk container special provisions (ADR) : TP1
- Tank code (ADR) : LGBF
- Vehicle for tank carriage : FL
- Transport category (ADR) : 3

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : 3YE

Transport by sea

Special provisions (IMDG) : 223
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Immiscible with water.

Air transport

Not regulated

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

AlphaChem 3 in 1 Wood Preserver Colours

Safety Data Sheet

according to Regulation (EU) 2015/830

VOC content : 795 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains PROPICONAZOLE(60207-90-1), M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE(52645-53-1). May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.