Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name Cromar Cromapol F Black, Cromar Cromapol Opaque

Product Code Black: APOLG/Bulk
Opaque: APORTL/Bulk

Unique Formula Identifier (UFI)

Black: E2H0-T0VU-800F-HXUV

Opaque: SFN0-N032-V00Q-8CK5

Nanoform The product does not contain nanoparticles.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified use(s)

The product is intended for professional use. An acrylic roof coating, one coat

waterproofing coat ideal for emergency repairs.

Uses advised against No information available.

1.3 Details of the supplier of the safety data sheet

Company Identification Cromar Building Products Limited

Units 1,3,4,5 Northside Industrial Park,

Selby Road Whitley Bridge North Yorkshire DN14 0GH United Kingdom 01977 663133

Telephone 01977 663133

E-mail (competent person) <u>sales@cromar.uk.com</u>

Distributed in the EU Cromar Ireland

133 Butterfield Park Rathfarnham, Dublin 14, D14AE22

Ireland

 Telephone
 00353 87 2528476

 E-mail
 info@cromar.ie

1.4 Emergency Telephone Number

Emergency Phone No. 01977 663133 Office hours (08:30 - 17:00)

+353 (1) 809 2166 8.00am. - 10.00pm 7 days per week

National Poisons Information Centre (Ireland)
+353 (1) 809 2566

Members of Public 24 hr. emergency p

+353 (1) 809 2566

24 hr. emergency phone number
Healthcare Professionals ONLY

+44 (0) 3448 920111

24 hr. emergency phone number

National Poisons Information Servce (Northern Ireland) +44 (0) 3448 920111 24 hr. emergency phone numbe

Healthcare Professionals ONLY

NHS 24 111 Members of Public

Language(s) spoken: English

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 3; H226 STOT SE 3; H336

Lact.; H362

Aquatic Chronic 2; H411

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product name Cromapol Mid Grey; Cromar Cromapol F White

Page: 1 of 9

Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Contains: Low Aromatic White Spirit; Chlorinated Paraffin; 2-Methoxy-1-Methylethyl

Acetate

Hazard Pictogram(s)







Signal Word(s) WARNING

Hazard Statement(s) H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness. H362: May cause harm to breast-fed children. H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) P201: Obtain special instructions before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray. P263: Avoid contact during pregnancy/while nursing.

P280: Wear protective gloves/protective clothing and eye/face protection. P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P273: Avoid release to the environment.

Supplemental information Not applicable

2.3 Other hazards None Known

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances - Not applicable

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
2-Methoxy-1-Methylethyl Acetate	20 - 25	108-65-6	203-603-9	01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336
Low Aromatic White Spirit	<10	64742-48-9	919-857-5	01-2119463258-33	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336
Chlorinated Paraffin	2.5 - <10	85535-85-9	287-477-0	01-2119519269-33	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Lact.; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Note: For full text of H phrases see section 16.

Cromar Cromapol



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Date of issue: 22nd February 2022 Version 1.0

4. **SECTION 4: FIRST AID MEASURES**



4.1 Description of first aid measures

Self-protection of the first aider Use personal protective equipment as required. Wear appropriate personal

> protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid breathing vapours. Avoid all contact. Contaminated clothing should be laundered before reuse. Avoid contact during pregnancy/while nursing.

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned:

Get medical advice/attention.

Skin contact IF ON SKIN: Remove contaminated clothing and wash all affected areas with

plenty of water. Wash contaminated clothing before reuse. IF exposed or

concerned: Get medical advice/attention.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If irritation (redness, rash, blistering) develops, get medical attention. IF exposed or concerned: Get

medical advice/attention.

Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Make victim drink

plenty of water. Do not give anything by mouth to an unconscious person. Call

a POISON CENTER/doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and

delayed

May cause drowsiness or dizziness. May cause harm to breast-fed children.

4.3 Indication of any immediate medical attention and

special treatment needed

Treat symptomatically.

Notes to a physician: IF INHALED: Respiratory symptoms, including pulmonary edema, may be

delayed.

5. **SECTION 5: FIREFIGHTING MEASURES**

5.1 Extinguishing media

> Suitable extinguishing media As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical,

foam or waterspray and sand.

Do not use water jet. Direct water jet may spread the fire. Unsuitable extinguishing media

5.2 Special hazards arising from the substance or Flammable liquid and vapour. May decompose in a fire giving off toxic fumes. mixture

Carbon monoxide, Carbon dioxide, organic and inorganic compounds.

5.3 Advice for firefighters Fire fighters should wear complete protective clothing including self-contained

breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Protect against electrostatic charges. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Avoid breathing vapours. Avoid contact during pregnancy/while nursing. See Section: 8

6.2 **Environmental precautions** Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Eliminate sources of ignition. Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill

Page: 3 of 9

Cromar Cromapol



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Date of issue: 22nd February 2022 Version 1.0

site after material pick-up is complete. Dispose of this material and its container

as hazardous waste

6.4 Reference to other sections See Section: 8, 13

7. **SECTION 7: HANDLING AND STORAGE**

7.1 Precautions for safe handling Avoid contact with skin. Ensure operatives are trained to minimise exposures. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not handle until all safety precautions have been read and understood. Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Take precautionary measures against static discharges. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2 Conditions for safe storage, including any

incompatibilities

Ground/bond container and receiving equipment. Use explosion-proof equipment. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Keep away from direct sunlight.

Storage temperature Ambient temperatures.

Incompatible materials Oxidizing agent; Strong acids; strong bases.

7.3 Specific end use(s) See Section: 1.2.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters**

8.1.1 Occupational exposure limits

			Limit Values					
EC No.	CAS No.	Name of the Chemical Agent	8 hours		Short-term		Notation	
			mg/m ³	ppm	mg/m³	ppm		
203-603-9	108-65-6	2-Methoxy-1-Methylethyl Acetate	275	50	550	100	The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

Source: SCOEL recommended OEL (2007b)

SUBSTANCE	CAS No.	LTEL (8 hr TWA	LTEL (8 hr TWA	STEL (ppm)	STEL (mg/m³)	Note
		ppm)	mg/m³)			
1-Methoxypropyl acetate	108-65-6	50	275	100	550	OELV
Carbon Black	1333-86-4	-	3	-	-	OELV
Talc						OELV
Total dust	14807-96-6	-	10	-	-	
Respirable dust		-	0.8	-	-	
(2-	34590-94-8	50	308	=	-	OELV
methoxymethylethoxy)						
propanol						

Source: OELV: Health and Safety Authority, Code of Practice, 2020

Substance	CAS No.	LTEL	LTEL	STEL	STEL	Note
Substance	CAS NO.	(8 hr TWA ppm)		(ppm)	(mg/m³)	Note

Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

			(8 hr TWA mg/m³)			
1-Methoxypropyl acetate	108-65-6	50	274	100	548	WEL, Sk
Carbon Black	1333-86-4	-	3.5	-	7	WEL
Talc, respirable dust	14807-96-6	=	1	-	-	WEL
Silica, respirable crystalline (respirable fraction)	-	-	0.1	-	-	WEL
(2-methoxymethylethoxy) propanol	34590-94-8	50	308	-	-	WEL, Sk
2-Dimethylaminoethanol	108-01-0	2	7.4	6	22	WEL

Source: WEL: Workplace Exposure Limit (UK HSE EH40)

Sk - Can be absorbed through skin.

8.1.2 Biological limit value Not established

8.1.3 PNECs and DNELs Not established

8.2 Exposure controls

8.2.1 Appropriate engineering controlsEnsure adequate ventilation. Atmospheric levels should be controlled in

compliance with the occupational exposure limit. A washing facility/water for eye

and skin cleaning purposes should be present.

8.2.2 Individual protection measures, such as personal

protective equipment

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid all contact. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection:

Wear impervious gloves (EN374). Protective index 6, corresponding > 480 minutes of permeation time according to EN 374 Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection:

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

Thermal hazards Not applicable

8.2.3 Environmental exposure controls Avoid release to the environment.

Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

9. **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Information on basic physical and chemical properties

> Physical state Viscous Liquid Colour Black; Opaque Odour Characteristic Melting point/freezing point No data available

Boiling point or initial boiling point and boiling range >35 °C

Flammability Flammable liquid Lower and upper explosion limit No data available Flash point 38 °C [Closed cup]

>200°C Auto-ignition temperature

No data available Decomposition temperature not applicable pН No data available Kinematic viscosity

Solubility The substance is not soluble in water.

No data available Partition coefficient: n-octanol/water (log value) No data available Vapour pressure

1 13 Density and/or relative density

Relative vapour density No data available Particle characteristics No data available

9.2 Other information None Known

10. **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity Stable under normal conditions. 10.2 **Chemical stability** Stable under normal conditions. Possibility of hazardous reactions 10.3 Stable under normal conditions.

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep away from direct sunlight. Extreme temperatures.

10.5 Incompatible materials Oxidizing agent; Strong acids; strong bases.

10.6 Hazardous decomposition products Flammable liquid and vapour. Combustion products: Carbon monoxide, Carbon

dioxide, organic and inorganic compounds. In use, may form flammable/explosive

vapour-air mixture.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in

Regulation (EC) No 1272/2008 **Acute toxicity - Ingestion** Acute toxicity - Inhalation Acute toxicity - Skin contact Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity

Reproductive toxicity

Aspiration hazard

Chlorinated Paraffin Lact.: H362: May cause harm to breast-fed children. Harmonised Classification

Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met.

Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met.

Mixture: Based upon the available data, the classification criteria are not met.

Mixture: Lact. May cause harm to breastfed babies.

STOT - Single Exposure Mixture: STOT SE 3: H336: May cause drowsiness or dizziness.

2-Methoxy-1-Methylethyl Acetate STOT SE 3: H336: May cause drowsiness or dizziness.

Expert judgement and weight of evidence.

Low Aromatic White Spirit STOT SE 3: H336: May cause drowsiness or dizziness.

Expert judgement and weight of evidence.

STOT - Repeated Exposure Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met.

Low Aromatic White Spirit Asp. Tox. 1: H304: May be fatal if swallowed and enters airways.

Page: 6 of 9

Cromar Cromapol



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Date of issue: 22nd February 2022 Version 1.0

Kinematic viscosity: 0.8 and 2.1 mm2/s

11.2 Information on other hazards11.2.1 Endocrine disrupting properties

Chlorinated Paraffin Priority List of Endocrine Disrupting Chemicals (EDCs) - Category 1

11.2.2 Other information None known

12. SECTION 12: ECOLOGICAL INFORMATION

12.	OLOTION 12. LOOLOGIOAL IIII OMINATION	
12.1	Toxicity Chlorinated Paraffin	Mixture: Aquatic Chronic 2; H411: Toxic to aquatic life with long lasting effects. Aquatic Acute 1; H400: Very toxic to aquatic life. Harmonised Classification EC50 (Daphnia magna) (48h): 0008 mg/l (OECD 202)
12.2	Persistence and degradability	Aquatic Chronic 1; H410: Very toxic to aquatic life with long lasting effects. Harmonised Classification NOEC (Daphnia magna) (21d): 0.01 mg/l (OECD 202) No data for the mixture as a whole.
	2-Methoxy-1-Methylethyl Acetate	Readily biodegradable.
	Low Aromatic White Spirit	Readily biodegradable.
	Chlorinated Paraffin	Biodegradability is retarded by increasing degree of chlorination, though biodegradation continued for even the highest chlorinated test material in an extended study. (OECD 301 D)
12.3	Bioaccumulative potential	No data for the mixture as a whole.
	2-Methoxy-1-Methylethyl Acetate	The substance has low potential for bioaccumulation.
	Low Aromatic White Spirit	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance
	Chlorinated Paraffin	The product has potential for bioaccumulation. Bioconcentration factor (BCF): 6660
12.4	Mobility in soil	No data for the mixture as a whole.
	•	
		Standard tests for this endpoint are intended for single substances and are not
	2011 / 1101101101 771110 00	appropriate for this complex substance
	Chlorinated Paraffin	The substance has low mobility in soil. Log Koc: 5.0 – 5.2
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Endocrine disrupting properties	
5		Priority List of Endocrine Disrupting Chemicals (EDCs) - Category 1
12.7	Other adverse effects	None known
,		

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste classification according to Directive 2008/98/EC (Waste Framework Directive)

This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility. Empty container may contain product residue which may result in flammable or explosive vapours inside the

container

Dispose of contents in accordance with local, state or national legislation.

Waste code: HP3 (Flammable)

14. SECTION 14: TRANSPORT INFORMATION

		ADR/RID	ADN	IMDG	IATA/ICAO	
14.1	UN number or ID number	UN 1263	UN 1263	UN 1263	UN 1263	
14.2	UN proper shipping name	PAINT RELATED	PAINT RELATED	PAINT RELATED	PAINT RELATED	
		MATERIAL	MATERIAL	MATERIAL	MATERIAL	
14.3	Transport hazard class(es)	3	3	3	3	
14.4	Packing group	III	III	III	III	

Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

14.5 **Environmental hazards** DANGEROUS FOR DANGEROUS FOR Classified as a Marine DANGEROUS FOR THE ENVIRONMENT THE ENVIRONMENT Pollutant. THE ENVIRONMENT

14.6 Special precautions for user See Section: 2 14.7 Not applicable

Maritime transport in bulk according to IMO instruments

Additional information None

SECTION 15: REGULATORY INFORMATION 15.

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

15.1.1 **EU** regulations

14.8

Authorisations and/or restrictions on use Not restricted

Substance(s) of Very High Concern (SVHCs) This product does not contain any known "substances of very high concern"

(SVHC's)

EU Seveso Directive (2012/18/EU) P5a FLAMMABLE LIQUIDS

E2 Hazardous to the Aquatic Environment in Category Chronic 2

To follow: Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of

workers from the risks related to chemical agents at work.

15.1.2 **National regulations** Not restricted

15.2 **Chemical Safety Assessment** A REACH chemical safety assessment has not been carried out.

16. **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: Not applicable – V1.0

References:

Existing Safety Data Sheet (SDS) for Cromar CROMAPOL.

Existing ECHA registration(s) for 2-Methoxy-1-Methylethyl Acetate (CAS No.108-65-6); Low Aromatic White Spirit (CAS No.64742-48-9); Chlorinated Paraffin (CAS No. 85535-85-9)

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification procedure
Flam. Liq. 3; H226	Flash point (°C) / Boiling Point (°C)
STOT SE 3; H336	Threshold Calculation
Lact.; H362	Threshold Calculation
Aquatic Chronic 2; H411	Threshold Calculation

Legend

ADR ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road ADN ADN: European Agreement on the International Transport of Dangerous Goods by Inland Waterways CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

DNEL Derived no effect level

IATA IATA: International Air Transport Association **ICAO** ICAO: International Civil Aviation Organization **IMDG** IMDG: International Maritime Dangerous Goods

LTEL Long term exposure limit

PBT PBT: Persistent, Bioaccumulative and Toxic

PNEC Predicted No Effect Concentration

Registration, Evaluation, Authorisation and Restriction of Chemicals REACH

RID RID: Regulations concerning the international railway transport of dangerous goods

STEL Short term exposure limit

vPvB vPvB: very Persistent and very Bioaccumulative

Page: 8 of 9

Cromar Cromapol



Date of issue: 22nd February 2022 Version 1.0

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Hazard classification / Classification code:

Flam. Liq. 3; Flammable liquid, Category 3 Asp. Tox. 1; Aspiration hazard, Category 1

Skin Irrit. 2; Skin corrosion/irritation, Category 2

Eye Irrit. 2; Eye Irritation, Category 2

STOT SE 3; Specific Target Organ Toxicity — Single Exposure,

Category 3

Lact.; Effects on or via lactation

Aquatic Acute 1; Hazardous to the aquatic environment, acute, Category

1

Aquatic Chronic 1; Hazardous to the aquatic environment, Chronic,

Category 1

Aquatic Chronic 2; Hazardous to the aquatic environment, Chronic ,

Category 2

Hazard Statement(s)

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Cromar Building Products Limited gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Cromar Building Products Limited accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

Exposure scenarios for substances in this preparation are not available.

Page: 9 of 9