

Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 1 of 13
Date Prepared: 14/07/2020

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1. Product identifier** Acrypol Rustkiller
Product Code: ACRY/RUSTKR
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Uses: Rust-preventing Primer
- 1.3. Details of the supplier of the safety data sheet**
Cromar Building Products, Units 3,4,5 Northside Ind Park, Whitley Bridge, Goole, DN14 0GH, United Kingdom
Tel: +44 (0) 1977 663 133 Fax: +44 (0) 1977 662 186
e-mail sales@cromar.uk.com
Web site www.acrypolproducts.co.uk
- 1.4. Emergency telephone number** +44 (0) 1977 663 133 (09:00 to 17:00 UK time)

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards STOT ES 3 - H335, H336
Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram



Signal word


Hazard statements

Warning

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take precautionary measures against static discharge.
P260 Do not breathe vapour/ spray.
P264 Wash contaminated skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 2 of 13
Date Prepared: 14/07/2020

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTRE/ doctor if you feel unwell.
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains Hydrocarbon, C9 Aromatic, HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclic, <2% aromatics.

2.3. Other hazards

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hydrocarbon, C9 Aromatic	10-30%
CAS number: 64742-95-6	EC number: 918-668-5
REACH registration number: 01-2119455851-35-XXXX	
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335, H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics	5-10%
<2 aromatics	
CAS number: --	EC number: 919-857-5
REACH registration number: 01-2119463258-33-XXXX	
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 3 of 13
Date Prepared: 14/07/2020

xylene		1-5%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX
Classification		
Flam. Liq. 3 - H226 Skin Irrit. 2 - H315		

Potassium Aluminium Silicate		<1%
CAS number: 12001-26-2		
Classification		
Not classified		

Ethanol		<1%
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-0000
Classification		
Flam. Liq. 2 - H225		

2-Butanone Oxime		<1%
CAS number: 1330-20-7	EC number: 202-496-6	REACH registration number: 01-2119539477-28-XXXX
Classification		
Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H 351		

Methanol		<1%
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44-0000
Classification		
Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370		

The full text for all R-Phrases and Hazard Statements and displayed in section 16.

SECTION 4. FIRST-AID MEASURES

4.1. Description of first aid measures

General information


If in doubt, get medical attention promptly. Never give anything by mouth to an unconscious person.

Inhalation

Move affected person to fresh air at once. If breathing stops, provide artificial respiration.

Ingestion

Get medical attention immediately. Keep affected person warm and at rest. Do not induce vomiting.



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 4 of 13
Date Prepared: 14/07/2020

Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause respiratory irritation. Prolonged or repeated exposure may cause the following adverse effects: Coughing. May cause nausea, headache, dizziness and intoxication.
Ingestion	Pneumonia may be the result if vomited material containing solvents reaches the lungs. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause stomach pain or vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation. Prolonged or repeated exposure may cause the following adverse effects: Pain or irritation. Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media


Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Fire-water run-off in sewers may create fire or explosion hazard. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Control run-off water by containing and keeping it out of sewers and watercourses.
Hazardous combustion Products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO). Acrid smoke or fumes. Metal oxide(s). Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 5 of 13
Date Prepared: 14/07/2020

Firefighting	In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Use protective equipment appropriate for surrounding materials.
For emergency responders	Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions


Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Contain spillage with sand, earth or other suitable non-combustible material.
---------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Small Spillages: Stop leak if safe to do so. Move containers from spillage area. Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers. Large Spillages: Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Move containers from spillage area. No smoking, sparks, flames or other sources of ignition near spillage. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste via a licensed waste disposal contractor. The contaminated absorbent may pose the same hazard as the spilled material.
-------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.
-----------------------------	---



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 6 of 13
Date Prepared: 14/07/2020

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Note:

The information in this section contains generic advice and guidance.

Usage precautions

For professional users only. Eliminate all sources of ignition. Use only in well-ventilated areas. Wear protective clothing as described in Section 8 of this safety data sheet. Earth container and transfer equipment to eliminate sparks from static electricity. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Use only non-sparking tools. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store at temperatures between 5°C and 25°C. Store in accordance with national regulations. Store in tightly-closed, original container. Avoid contact with oxidising agents. Avoid contact with acids and alkalis. Read label before use. Avoid exposure to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly sealed when not in use.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits

Hydrocarbon, C9 Aromatic

Long-term exposure limit (8-hour TWA): WEL 100 mg/m³


HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 7 of 13
Date Prepared: 14/07/2020

Sk

Potassium Aluminium Silicate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust
Long-term exposure limit (8-hour TWA): WEL 0.8 mg/m³ respirable dust

ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

2-butanone oxime

Long-term exposure limit (8-hour TWA): 10 ppm

methanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³
Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Hydrocarbon, C9 Aromatic (CAS: 64742-95-6)

DNEL - Dermal; Long term : 25 mg/kg/day
- Inhalation; Long term : 150 mg/m³

HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

DNEL Industry - Dermal; Long term : 208 mg/kg/day
Industry - Inhalation; Long term : 871 mg/m³

xylene (CAS: 1330-20-7)

DNEL Workers - Inhalation; Long term systemic effects: 77 mg/m³
Workers - Inhalation; Short term systemic effects: 289 mg/m³
Workers - Inhalation; Short term local effects: 289 mg/m³

PNEC - Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

ethanol (CAS: 64-17-5)


DNEL Industry - Inhalation; Short term local effects: 1900 mg/m³
Industry - Dermal; Long term systemic effects: 343 mg/kg/day
Industry - Inhalation; Long term systemic effects: 950 mg/m³

PNEC - Fresh water; Long term 0.96 mg/l
- Marine water; Long term 0.79 mg/l
- Sediment; Long term 3.6 mg/kg
- Soil; Long term 0.63 mg/kg

2-butanone oxime (CAS: 96-29-7)

DNEL Workers - Inhalation; Long term systemic effects: 9 mg/m³
Workers - Inhalation; Long term local effects: 3.33 mg/m³
Workers - Dermal; Long term systemic effects: 1.3 mg/kg/day
- Dermal; Short term systemic effects: 2.5 mg/kg/day

PNEC - Fresh water; 0.256 mg/l



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 8 of 13
Date Prepared: 14/07/2020

		- Intermittent release; 0.118 mg/l - STP; 177 mg/l
		COBALT BIS(2-ETHYLHEXANOATE) (CAS: 136-52-7)
DNEL		Workers - Inhalation; Long term local effects: 235.1 µg/m ³ General population - Inhalation; Long term local effects: 37 µg/m ³ General population - Oral; Long term systemic effects: 55.8 mg/kg/day
PNEC		- Fresh water; 0.6 µg/l - Marine water; 2.36 µg/l - STP; 0.37 mg/l - Sediment (Freshwater); 9.5 mg/kg dwt - Sediment (Marinewater); 9.5 mg/kg dwt - Soil; 10.9 mg/kg dwt
		methanol (CAS: 67-56-1)
DNEL		Industry - Dermal; Short term systemic effects: 40 mg/kg/day Industry - Dermal; Long term systemic effects: 40 mg/kg/day Industry - Inhalation; Short term systemic effects: 260 mg/m ³ Industry - Inhalation; Short term local effects: 260 mg/m ³ Industry - Inhalation; Long term systemic effects: 260 mg/m ³ Industry - Inhalation; Long term local effects: 260 mg/m ³
PNEC		- Fresh water; 154 mg/l - Marine water; 15.4 mg/l - Soil; 23.5 mg/kg - STP; 100 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering
Controls


As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 9 of 13
Date Prepared: 14/07/2020

Other skin and body Protection	properties and change them as soon as any deterioration is detected.
Hygiene measures	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for information on material and design requirements and test methods.
Respiratory protection	Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Environmental exposure Controls	Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator.
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Red.
Odour	Characteristic.
Flash point	21-32 °C
Relative Density	1.29 +/- 0.1kg/L
Solubility(ies)	Immiscible in water

9.2. Other information

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	--



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 10 of 13
Date Prepared: 14/07/2020

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous Reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the accumulation of vapours in low or confined areas.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Products Does not decompose when used and stored as recommended.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity - dermal

ATE dermal (mg/kg) 58,965.42

Acute Toxicity - inhalation

ATE inhalation (gasses ppm) 268,024.66

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil


12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

General information Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 11 of 13
Date Prepared: 14/07/2020

Disposal methods	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains.
Waste class	08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)


ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 12 of 13
Date Prepared: 14/07/2020

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Health and environmental Listings	None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.


SECTION 16. OTHER INFORMATION

Abbreviations and acronyms used in the safety data sheet

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number

Revision date 14/07/2020

Revision 5



Product:
Supersedes: Version Dated 27/06/2018

Acrypol Rustkiller
Version: 5

Page 13 of 13
Date Prepared: 14/07/2020

SDS number	5358
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H370 Causes damage to organs . H411 Toxic to aquatic life with long lasting effects. EUH208 Contains 2-butanone oxime. May produce an allergic reaction.
Description	Rust Stabilising Primer
Mix Ratio	Single Pack
Shelf life	2 years
EU Dir 2	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.
