

Cromaslate offers a Great Alternative to Natural Slate.

Features and benefits

- Lightweight
- Easy fixing
- 5mm spacer
- 40 years life expectancy
- 100% Recyclable
- BS476 Part 3 Fire rating EXT.S.AC
- BRE Wind and Rain to EN15601.
- Textured finish for the natural slate look.
- Easy to cut with fine tooth hand saw
- No Grading
- No Drilling

Suitable

- Conservatories
- Pitched roofs
- Lean to roofs
- Minimum pitch 15°
- Maximum Pitch 90°

Material

- Recycled Polypropylene with UV.

Storage

- Minimum 7 degrees
- Fixing 0 degrees

Technical Data

- Maximum gauge 200 mm
- Minimum Pitch 15°
- Maximum Pitch 90°
- Slate Size 425mm x 330mm
- Weight per slate 650 grams
- Packaged in bundles of 15 (1m²)
- Bundle weight 9.75 kg
- Bundles per pallet 54
- Pallet quantities 810 Slates
- Pallet Weight 534 kg.

Colours Available

- Slate Grey
- Grey
- Black

Fixings

- Corrosive resistant 30mm large head ring shank nails or screws
- 25 x 50mm battens
- 18mm Plywood/OSB

Associated products

- Cromar Vent 3 membrane
- Cromar Eaves ventilation
- Cromar Pro dry ridge system.

- **Ridge tiles**
Newly designed ridge tiles that are manufactured with the Cromaslate to match with texture and colours , with a 225mm visible face.
Size 300mm x 490mm
- **Ridge Tile System 2**
The ridge tile system 2 provides an attractive uniform alternative finish to the standard ridge giving customer choice and satisfaction. Come with it's own end ridge caps. With a colour match of the slates.
Size: 330mm x 170mm

