

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758



Date of issue: 28.07.2022
Version 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	Product name	AlphaChem Plasterers Enhanced Grit
	Product Code	MPG/Bulk
	Unique Formula Identifier (UFI)	NXF0-70WP-9001-XH91
	Nanoform	The product does not contain nanoparticles.
1.2 Relevant identified uses of the substance or mixture and uses advised against	Identified Use(s)	Professional use, industrial use. Plaster bonding agent with added fine aggregate for key to surfaces. Adhesives, binding agents.
	Uses advised against	Anything other than the above.
1.3 Details of the supplier of the safety data sheet	Company Identification	Cromar Building Products Limited Units 1,3,4,5 Northside Industrial Park, Selby Road Whitley Bridge North Yorkshire DN14 0GH United Kingdom 01977 663133 sales@cromar.uk.com
	Telephone	
	E-mail (competent person)	
1.4 Emergency telephone number	Emergency Phone No.	01977 663133
	National Poisons Information Service (United Kingdom)	+44 (0) 3448 920111
	NHS 24	111
	Languages spoken	English
		Office hours (08:30 - 17:00) 24 hr. emergency phone number Healthcare Professionals ONLY Members of Public

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
2.1.1 The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3;H412
2.2 Label elements	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain Plasterers Enhanced Grit Calcium Oxide
Product name	
Contains:	
Hazard Pictogram(s)	
Signal Word(s)	DANGER
Hazard Statement(s)	H315: Causes skin irritation. H318: Causes serious eye damage. H412: Harmful to aquatic life with long lasting effects.
Precautionary Statement(s)	P264: Wash hands and exposed skin thoroughly after handling.

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758

P280: Wear protective gloves/protective clothing and eye/face protection.
P310: Immediately call a POISON CENTER/doctor/...
P302+P352: IF ON SKIN: Wash with plenty of water.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental information

None Known

2.3 Other hazards

None Known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Not applicable

3.2 Mixtures

Classification: The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain

Chemical identity of the substance	%W/W	CAS No.	EC No.	UK-REACH Registration No.	Hazard classification
Silica Oxide	10 - 15	112945-52-5	601-216-3	Not yet assigned in the supply chain	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335
Calcium Oxide	3 - 5	1305-78-8	215-138-9	Not yet assigned in the supply chain	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335
Copper Oxide	0.01 – 0.1	1317-38-0	215-269-1	Not yet assigned in the supply chain	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M=100 M(Chronic)=10
Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one	< 0.001	55965-84-9	911-418-6	Not yet assigned in the supply chain	Acute Tox. 3; H301 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M=100 M(Chronic)=100

For full text of H phrases see section 16.

SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Self-protection of the first aider

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Do not breathe vapour. Avoid all contact. Contaminated clothing should be laundered before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Remove patient from exposure, keep warm and at rest. Call a POISON CENTER/doctor if you feel unwell.

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758

Date of issue: 28.07.2022
Version 1.0

Skin contact	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF IN EYES: Treatment by an ophthalmologist due to possible caustic burn of the eyes may be required.
Ingestion	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Make victim drink plenty of water. Do not give anything by mouth to an unconscious person. Call a POISON CENTER/doctor if you feel unwell.
4.2 Most important symptoms and effects, both acute and delayed	Causes skin irritation. Causes damage to the eyes.
4.3 Indication of any immediate medical attention and special treatment needed	Treat symptomatically.
Notes to a physician:	IF IN EYES: Treatment by an ophthalmologist due to possible caustic burn of the eyes may be required.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media	Extinguish with carbon dioxide, dry chemical, foam or waterspray and aqueous film forming foam.
Suitable extinguishing media	
Unsuitable extinguishing media	Do not use water jet. Direct water jet may spread the fire.
5.2 Special hazards arising from the substance or mixture	Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions. In case of fire: Carbon oxides may be formed.
5.3 Advice for firefighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Keep upwind. Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Do not breathe vapour. See Section: 8
6.2 Environmental precautions	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
6.3 Methods and material for containment and cleaning up	Absorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Collect in closed and suitable containers for disposal. Ventilate the area and wash spill site after material pick-up is complete.
6.4 Reference to other sections	See Section: 8, 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	Ensure adequate ventilation. Do not breathe vapour. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Ensure operatives are trained to minimise exposures. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Remove contaminated clothing and wash clothing before reuse. See Section: 8.
7.2 Conditions for safe storage, including any incompatibilities	Ground/bond container and receiving equipment. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight.
storage temperature	Keep cool. Protect from sunlight.
Incompatible materials	Strong acids, strong bases.
7.3 Specific end use(s)	See Section: 1.2.

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters 8.1.1 Occupational exposure limits

United Kingdom:

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Calcium Oxide	1305-78-8	-	2 1	-	- 4	Respirable fraction

Source: WEL: Workplace Exposure Limit (UK HSE EH40).

Note:

Carc - Capable of causing cancer and/or heritable genetic damage.

Sk - Can be absorbed through skin.

BMGV – Biological monitoring guidance value.

Ireland

SUBSTANCE	CAS No.	Occupational Exposure Limit Value (8-hour reference period)		Occupational Exposure Limit Value (15-minute reference period)		Notes
		ppm	mg/m ³	ppm	mg/m ³	
Calcium Oxide	215-138-9	-	1 (R)	-	4 (R)	IOELV
Zinc Oxide	1314-13-2	-	2 (R)	-	10	-

Source: 2021 Code of Practice for Safety, Health and Welfare at Work (Chemical Agents) Regulation (2001 – 2021) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001 – 2019); Health and Safety Authority

Note:

IOELV: Indicative Occupational Exposure Limit Value

(R): Respirable Fraction

8.1.2 Biological limit value Not established

8.1.3 PNECs and DNELs Not established

8.2 Exposure controls

8.2.1 Appropriate engineering controls Ensure adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 Individual protection measures, such as personal protective equipment General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid all contact. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection.

Skin protection

Hand protection:

Wear impervious gloves. Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758



Date of issue: 28.07.2022
Version 1.0



Respiratory protection

Body protection:

Wear work clothes with long sleeves. Wear chemical resistant apron.



Thermal hazards

In case of inadequate ventilation wear respiratory protection.

Not applicable

8.2.3 Environmental exposure controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Viscous orange liquid
Odour	Characteristic
Odour threshold	No data available
pH	No data available
Melting point/freezing point	No data available
Initial boiling point and boiling range	100 °C
Flash point	> 93 °C
Evaporation rate	No data available
Flammability (solid, gas)	Not flammable
Upper/lower flammability or explosive limits	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	1.03 (@ 20°C)
Solubility(ies)	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Explosive properties	Not explosive
Oxidising properties	No data available

9.2 Other information

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Stable under normal conditions.
10.4 Conditions to avoid	Keep only in original container. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Keep away from direct sunlight.
10.5 Incompatible materials	Keep cool. Protect from sunlight.
10.6 Hazardous decomposition products	In case of fire: Carbon oxides may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion

Mixture: Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LD50 (oral,rat) mg/kg: > 2.000 mg/kg bw

Acute toxicity - Inhalation

Mixture: Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 (rat) mg/m³ >1.000

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758

Date of issue: 28.07.2022
Version 1.0

Acute toxicity - Skin contact	Mixture: Based upon the available data, the classification criteria are not met. Mixture: Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LD50 (skin,rabbit) mg/kg: >5.000
Skin corrosion/irritation	Mixture: Skin Irrit. 2; H315: Causes skin irritation. Silica Oxide Skin Irrit. 2; H315: Causes skin irritation. Source: EU classification and labelling inventory Calcium Oxide Skin Irrit. 2; H315: Causes skin irritation. Based on the results of the study described in this report and according to the Directive 67/548/EEC and subsequent regulations, calcium hydroxide (hydrated lime) in putty form (60 % H ₂ O, 40 % Ca(OH) ₂), shall be classified as irritating to the skin but shall not be classified as corrosive. Source: ECHA registration dossier
Serious eye damage/irritation	Mixture: Eye Dam. 1; H318: Causes serious eye damage. Silica Oxide Eye Irrit. 2; H319: Causes serious eye irritation. Source: EU classification and labelling inventory Calcium Oxide Eye Dam. 1; H318: Causes serious eye damage. Under the given experimental conditions the product calcium oxide is considered as an irritant to the eye in rabbits. According to the Directive 67/548/EEC and subsequent regulations, the classification of the product, calcium oxide, should be "risk of serious damage to eyes". According to the EC Regulation No. 1272/2008 and subsequent regulations, the test item is classified as Category 1. Source: ECHA registration dossier
Respiratory or skin sensitisation	Mixture: Based upon the available data, the classification criteria are not met.
Germ cell mutagenicity	Mixture: Based upon the available data, the classification criteria are not met.
Carcinogenicity	Mixture: Based upon the available data, the classification criteria are not met.
Reproductive toxicity	Mixture: Based upon the available data, the classification criteria are not met.
STOT - Single Exposure	Mixture: Based upon the available data, the classification criteria are not met.
STOT - Repeated Exposure	Mixture: Based upon the available data, the classification criteria are not met.
Aspiration hazard	Mixture: Based upon the available data, the classification criteria are not met.
11.2 Other information	None Known

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Mixture: Aquatic Chronic 3; H412: Harmful to aquatic life with long lasting effects. Estimated LC50 (96h) : >100 mg/l. Aquatic Acute 1; H400: Very toxic to aquatic life. Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one Aquatic Chronic 1; H410: Very toxic to aquatic life with long lasting effects. LC50: 0.19 mg/L ECHA registration dossier Copper Oxide NOEC/(L)EC10 (freshwater fish): 2.2 µg/l – 188 µg/l ECHA registration dossier
12.2 Persistence and degradability	Based upon the available data, the classification criteria are not met. Silica Oxide Not applicable for inorganic substances. Source: ECHA registration dossier for sodium hydroxide Calcium Oxide Not applicable for inorganic substances. Source: ECHA registration dossier Copper Oxide Not applicable for inorganic substances. Source: ECHA registration dossier Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one Inherently Biodegradable Source: ECHA registration dossier
12.3 Bioaccumulative potential	Based upon the available data, the classification criteria are not met. Silica Oxide No information available. Not relevant Calcium Oxide Source: ECHA registration dossier

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758



Date of issue: 28.07.2022
Version 1.0

	Copper Oxide	Bioaccumulation will not occur Source: ECHA registration dossier
	Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one	Bioaccumulation will not occur BCF: 40-50 (@ 20 °C) Source: ECHA registration dossier
12.4	Mobility in soil	Based upon the available data, the classification criteria are not met.
	Silica Oxide	No information available.
	Calcium Oxide	No information available.
		Slightly mobile
	Copper Oxide	Kd soil: 2120 L/kg Source: ECHA registration dossier
	Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one	Highly Mobile KOC (Adsorption): 7,7 Source: ECHA registration dossier
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None Known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	
	Waste classification according to Directive 2008/98/EC (Waste Framework Directive)	This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility.
13.2	Additional information	None Known

SECTION 14: TRANSPORT INFORMATION

Not classified according to the United Nations 'Recommendations on the Transport of Dangerous Goods'.

	ADR/RID	IMDG	IATA/ICAO
14.1	UN number	None assigned	None assigned
14.2	UN proper shipping name	None assigned	None assigned
14.3	Transport hazard class(es)	None assigned	None assigned
14.4	Packing group	None assigned	None assigned
14.5	Environmental hazards	Not classified	Not classified as a Marine Pollutant.
14.6	Special precautions for user	See Section: 2	
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable	

SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1	EU regulations	
	Authorisations and/or restrictions on use	Not restricted
	GB regulations	
	Grandfathered registrations notified substances list	Calcium Oxide: Restricted substances Cooper Oxide: Restricted substances
15.1.2	National regulations	Not restricted
15.2	Chemical Safety Assessment	A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Not applicable – V1.0

References:

Existing Safety Data Sheet (SDS) for Silica Oxide (CAS No. 112945-52-5).

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758



Date of issue: 28.07.2022
Version 1.0

Existing ECHA registration(s) for Calcium Oxide (CAS No. 1305-78-8), Copper Oxide (CAS No. 1317-38-0) and Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one (CAS No. 55965-84-9)

Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830. Compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Classification of the substance or mixture. The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain	Classification procedure
Skin Irrit. 2; H315	Additivity Method
Eye Dam. 1; H318	Threshold Calculation
Aquatic Chronic 3; H412	Summation Calculation

Legend

ADR	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioaccumulation Factor
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DNEL	Derived no effect level
IATA	IATA: International Air Transport Association
ICAO	ICAO: International Civil Aviation Organization
IMDG	IMDG: International Maritime Dangerous Goods
Kd	Soil adsorption coefficient
LTEL	Long term exposure limit
PBT	PBT: Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	RID: Regulations concerning the international railway transport of dangerous goods
STEL	Short term exposure limit
vPvB	vPvB: very Persistent and very Bioaccumulative

Hazard classification / Classification code:

Acute Tox. 3; Acute Toxicity, Category 3
Acute Tox. 2; Acute Toxicity, Category 2
Skin Corr. 1C; Skin corrosion/irritation, Category 1C
Skin Irrit. 2; Skin corrosion/irritation, Category 2
Skin Sens. 1A; Skin Sensitisation, Category 1A
Eye Dam. 1; Eye damage, category 1
Eye Irrit. 2; Eye Irritation, Category 2
Acute Tox. 2; Acute Toxicity, Category 2
STOT SE 3; Specific Target Organ Toxicity — Single Exposure, Category 3
Aquatic Acute 1; Hazardous to the aquatic environment, acute, Category 1

Hazard Statement(s)

H301: Corrosive to the respiratory tract.
H301: Toxic if swallowed.
H310: Fatal in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H330: Fatal if inhaled.
H335: May cause respiratory irritation.
H400: Very toxic to aquatic life.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Cromar Building Products gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Cromar Building Products accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

Exposure scenarios for substances in this preparation are not available.

SAFETY DATA SHEET

ALPHACEM PLASTERERS ENHANCED GRIT

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830
AS AMENDED BY UK REACH REGULATIONS SI 2019/758



Date of issue: 28.07.2022
Version 1.0