

Vent 3® AIR®

DECLARATION OF PERFORMANCE No. 32310777

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	32310777
2	INTENDED USE/S	Under roof covering of discontinuous roofs of buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	3
6a	HARMONISED STANDARD:	EN 13859-1:2014
	Notified body/ies:	0799, 1508

Declaration of Performance

Vent® 3 AIR
32310777
2025/09 , ver. 01
1810

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to Fire	E	3	
Length	50 m	3	
Width	1 m	3	
Resistance to water penetration:			
- before artificial ageing	W1	3	
- after artificial ageing	W1	3	
Tensile strength			
Longitudinal before ageing	330 (± 30) N/50 mm	3	
Longitudinal before ageing	280 (± 30) N/50 mm	3	
Transverse before ageing	270 (± 30) N/50 mm	3	
Transverse before ageing	225 (± 30) N/50 mm	3	
Resistance to tearing - longitudinal	210 (± 15) N	3	EN13859-1: 2014
Resistance to tearing – transverse	210 (± 15) N	3	
Elongation in longitudinal direction before ageing	56 (± 30) %	3	
Elongation in longitudinal direction after ageing	39 (± 30) %	3	
Elongation in transverse direction before ageing	68 (± 30) %	3	
Elongation in transverse direction after ageing	48 (± 30) %	3	
Water vapour transmission	Sd = 0.01 m	3	
Air permeability	50 (± 10) m/s	3	
Flexibility at low temperatures	NPD	3	
Dangerous substances	Less than 0.2 ppm	3	

Declaration of Performance

Vent 3® AIR
32310777
2025/09 , ver. 01
1810

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 26 September 2025



Name : Kim Knowlson
Function: Product Manager
At Whitley on 01 October 2025

.....K Knowlson

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Vent 3® AIR
32310777
2025/09 , ver. 01
1810



25

Sika Services AG, Zurich, Switzerland

DoP No. 32310777

EN13859-1:2014

Notified Body 0799, 1508

Under roof covering of discontinuous roofs of buildings

Reaction to Fire	E
Length	50 m
Width	1 m
Resistance to water penetration:	
- before artificial ageing	W1
- after artificial ageing	W1
Tensile strength	
Longitudinal before ageing	330 (± 30) N/50 mm
Longitudinal before ageing	280 (± 30) N/50 mm
Transverse before ageing	270 (± 30) N/50 mm
Transverse before ageing	225 (± 30) N/50 mm
Resistance to tearing - longitudinal	210 (± 15) N
Resistance to tearing – transverse	210 (± 15) N
Elongation in longitudinal direction before ageing	56 (± 30) %
Elongation in longitudinal direction after ageing	39 (± 30) %
Elongation in transverse direction before ageing	68 (± 30) %
Elongation in transverse direction after ageing	48 (± 30) %
Water vapour transmission	Sd = 0.01 m
Air permeability	50 (± 10) m/s
Flexibility at low temperatures	NPD
Dangerous substances	Less than 0.2 ppm

<http://dop.sika.com>**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Vent 3® AIR

32310777

2025/09 , ver. 01

1810

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Vent 3® AIR
32310777
2025/09 , ver. 01
1810

Declaration of Performance

Vent 3® AIR

32310777

2025/09 , ver. 01

1810